


# Tagora Incasso 970 - LED 3000K-Dali-SwitchDim- Verde

S./R. Cornelissen



IP20  Dimmerabile:



## LUMINAIRE

- Power Supply: **Alimentazione elettronica 220-240Vac 50/60Hz inclusa**
- Watt : **84W**
- Tensione di alimentazione: **220V-240V**
- Flusso luminoso emesso: **6425lm**
- CCT: **3000K**
- Efficiency: **54%**
- Efficacy: **76.49lm/W**
- CRI: **80**
- Dimmable Typology: **Dali**

## DESCRIZIONE

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. Consists of a trimless recessed frame fitted into the ceiling and an optical unit with an aluminium body painted in a range of colours: beige/white, grey/white, black/orange, black/vert and black/blue. Tagora 80 and 270 offer a high-output spot light with aluminium optics. Tagora 270 uses a proprietary system based on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use high-output sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. Only ceiling recessed installation allowed. Compliant with standard EN60598-1 and other specific standards.

**CODICE PRODOTTO: M250041**

## CARATTERISTICHE

- Codice articolo: **M250041**
- Colore: **Verde**
- Materiale: **Alluminio**
- Serie: **Architectural Indoor**
- design by: **S./R. Cornelissen**

## DIMENSIONI

- Diametro: **cm 104.6**
- Diametro incasso: **cm 100.2**
- Profondità incasso: **cm 22.7**
- Forma incasso: **Tonda**
- Peso: **cm 21**
- Prova del filo incandescente: **650°**

## SORGENTI INCLUSE

- Categoria: **Led**
- Numero: **1**
- Watt: **84W**
- Temperatura Colore (K): **3000K**
- CRI: **80**
- Color Tolerance: **MacAdam 3SDCM**
- Service Life: **L70 (6K) 50000h**