





# Vector Track 55 32° 4000K Undimmable Brushed Bronze

Carlotta de Bevilacqua



IP20   



## LUMINAIRE

- Watt: **25W**
- Lichtstrom (lm): **1622lm**
- CCT: **4000K**
- Efficiency: **68%**
- Efficacy: **64.87lm/W**
- CRI: **90**

## Anmerkungen

220/240Vac 50/60Hz Electronic ballast included.

## BESCHREIBUNG

Three sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Vector 55 track DALI zoom optic (22°-32°). Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 95 available only in track version. Version with compact 4-conductor (3p+n) adapter with hidden LED driver and not-dimmable phase selector.

## ARTIKELNUMMER: AN15320

## FUNKTIONEN

- Artikelnummer: **AN15320**
- Farbe: **Brushed Bronze**
- Installation: **ProjectorStromschiene**
- Serie: **Architectural Indoor**
- Anwendungsbereich: **Innenbeleuchtung**
- design: **Carlotta de Bevilacqua**

## DIMENSION

- Höhe: **cm 18.1**
- Breite: **cm 5.5**
- Länge Fuß: **cm 16.2**
- Neigung: **-90+90**
- Drehung: **360°**

## INKLUSIVE LICHTQUELLEN

- Kategorie: **Led**
- Anzahl: **1**
- Watt: **25W**
- Farbtemperatur(K): **4000K**

ZUBEHÖR



Accessories holder - Vector 55  
AP91100



Lens for elliptical emission - Vector 55  
AP91200



Soft filter - Vector 55  
AP91300



Anti-dazzle louvre - Vector 55  
AP91400



Adjustable dowsers - Vector 55  
AP91500