



# Vector Track 95 24° 2700K Undimmable Brushed bronze

Carlotta de Bevilacqua



IP20   



## LUMINAIRE

- Watt: **30W**
- Lichtstrom (lm): **2602lm**
- CCT: **2700K**
- Efficiency: **79%**
- Efficacy: **86.75lm/W**
- CRI: **90**

## Anmerkungen

220/240Vac 50/60Hz Electronic ballast included.

## BESCHREIBUNG

Three sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Vector 55 track DALI zoom optic (22°-32°). Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 95 available only in track version. Version with compact 4-conductor (3p+n) adapter with hidden LED driver and not-dimmable phase selector.

**ARTIKELNUMMER: AN21220**

## FUNKTIONEN

- Artikelnummer: **AN21220**
- Farbe: **Brushed Bronze**
- Installation: **ProjectorStromschiene**
- Serie: **Architectural Indoor**
- Anwendungsbereich: **Innenbeleuchtung**
- design: **Carlotta de Bevilacqua**

## DIMENSION

- Höhe: **cm 27.3**
- Breite: **cm 9.5**
- Länge Fuß: **cm 8.8**
- Neigung: **-90+90**
- Drehung: **360°**

## INKLUSIVE LICHTQUELLEN

- Kategorie: **Led**
- Anzahl: **1**
- Watt: **35W**
- Farbtemperatur(K): **2700K**

ZUBEHÖR



Adjustable dowsers  
M059910



Lens for elliptical emission  
M282007



Anti-dazzle louvre  
M282100



Accessories holder - Vector 95  
AP92100



Soft filter  
M056807