




Vector Track 95 60° 2700K Undimmable Brushed silver

Carlotta de Bevilacqua



IP20   



LUMINAIRE

- Watt: **30W**
- Lichtstrom (lm): **2559lm**
- CCT: **2700K**
- Efficiency: **78%**
- Efficacy: **85.3lm/W**
- CRI: **90**

Anmerkungen

220/240Vac 50/60Hz Electronic ballast included.

BESCHREIBUNG

Three sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Vector 55 track DALI zoom optic (22°-32°). Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 95 available only in track version. Version with compact 4-conductor (3p+n) adapter with hidden LED driver and not-dimmable phase selector.

ARTIKELNUMMER: AN21315

FUNKTIONEN

- Artikelnummer: **AN21315**
- Farbe: **Brushed Silver**
- Installation: **ProjectorStromschiene**
- Serie: **Architectural Indoor**
- Anwendungsbereich: **Innenbeleuchtung**
- design: **Carlotta de Bevilacqua**

DIMENSION

- Höhe: **cm 27.3**
- Breite: **cm 9.5**
- Länge Fuß: **cm 8.8**
- Neigung: **-90+90**
- Drehung: **360°**

INKLUSIVE LICHTQUELLEN

- Kategorie: **Led**
- Anzahl: **1**
- Watt: **35W**
- Farbtemperatur(K): **2700K**

ZUBEHÖR



Adjustable dowsers
M059910



Lens for elliptical emission
M282007



Anti-dazzle louvre
M282100



Accessories holder - Vector 95
AP92100



Soft filter
M056807