

# A.39 Suspension/Ceiling - Direct Emission - 2368mm - 20° - 3000K - Undimmable - 6x4 Optics - White

Carlotta de Bevilacqua



IP 20   



## LUMINARIA

- Potencia (W): **75W**
- Flujo Luminoso (lm): **4945lm**
- CCT: **3000K**
- Efficiency: **76%**
- Efficacy: **65.94lm/W**
- CRI: **90**

## Notas

Louvers supplied separately.  
APP interface supplied separately.  
The APP driver can not be controlled by DALI dimming system and viceversa.

## ESPECIFICACIONES

Optimized version in line applications with wide lengths. Diffusing direct and direct + indirect emission. Recessed trim, trimless, suspension and ceiling versions. Dimmable and non dimmable in two CCT 3000K and 4000K versions.

**CÓDIGO PRODUCTO: BH02001**

## CARACTERÍSTICAS

- Código del artículo: **BH02001**
- Color: **White**
- Instalación: **SuspensiónTecho**
- Serie: **Architectural Indoor**
- diseño: **Carlotta de Bevilacqua**

## DIMENSIONES

- Longitud: **cm 237**
- Ancho: **cm 4.5**
- Altura: **cm 8.5**

## FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **80W**
- Temperatura de Color (K): **3000K**
- Color Tolerance: **MacAdam 2SDCM**
- Service Life: **L90 (20K) 118000h**

**ACCESORIOS**



Louvre - 2368mm 6x4 optics - white AE43001



Louvre - 2368mm 6x4 optics black AE43004

NO  
IMAGE  
AVAILABLE

A.39 - Mechanical joint including 1 suspension cable AT09500



Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses. AF06000

NO  
IMAGE  
AVAILABLE

Angle louvre - 90° corner screen (on same plane) - White BH44001

NO  
IMAGE  
AVAILABLE

A.39 - Ceiling bracket and mechanical joint AT09501

NO  
IMAGE  
AVAILABLE

BLL interface for APP with antenna (Up to 40 addresses) DV1054APP

NO  
IMAGE  
AVAILABLE

Angle louvre - 90° corner screen (on same plane) - Black BH44004

NO  
IMAGE  
AVAILABLE

A.39 - End Ceiling Bracket (2x) AT09502

NO  
IMAGE  
AVAILABLE

A.39 - Dimmable APP Feeding kit including 2 suspension cables (5 poles) 2000m (H) AT10500APP

NO  
IMAGE  
AVAILABLE

A.39 - Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400

NO  
IMAGE  
AVAILABLE

A.39 - Suspension/Ceiling - End Caps (2pcs) - White BH16401