


# Algoritmo Stand-Alone - Wall/ceiling - white LED diffused emission - 68W 4000K DALI - White

Carlotta de Bevilacqua  
Paola di Arianello



IP20  Regulable: 



## LUMINARIA

- Potencia (W): **68W**
- Flujo Luminoso (lm): **4106lm**
- CCT: **4000K**
- Efficiency: **45%**
- Efficacy: **60.38lm/W**
- CRI: **80**
- Dimmable Typology: **Dali**

## ESPECIFICACIONES

Series of single units, preconfigured and complete for suspension-mounting, wall-mounting and ceiling-mounting. Body in extruded aluminium, painted white. Two lengths available: 1188 mm and 2372mm. LED version direct emission, diffused: LED monochromatic warm white (3000 K) and neutral white (4000 K). Power supply and light management system included, non dimmable or Dali-SwitchDim. Suspended version direct or double emission. Luminaires come complete with end caps, fixing brackets or suspension cables and optics. Compliant with standard EN60598-1 and other specific standards.

**CÓDIGO PRODUCTO: M2915N21**

## CARACTERÍSTICAS

- Código del artículo: **M2915N21**
- Color: **White**
- Instalación: **ParedTecho**
- Material: **Extruded Aluminium**
- Serie: **Architectural Indoor**
- Entorno de uso: **Interior**
- diseño: **Carlotta de Bevilacqua, Paola di Arianello**

## DIMENSIONES

- Longitud: **cm 237**
- Ancho: **cm 4.5**
- Altura: **cm 11**
- Peso: **cm 7.1**
- Prueba calorífica: **650°**

## FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **68W**
- Temperatura de Color (K): **4000K**
- Color Tolerance: **MacAdam 3SDCM**
- Service Life: **L70 (4K) 60500h**