

Algoritmo System for projectors - Pre-Wired gear for PAD and PAD Square - Direct + indirect emission LED 4000K Non dimmable

Carlotta de Bevilacqua
Paola di Arianello



IP40 

LUMINAIRE

- Power Supply: **Electronique Intégré**
- Watt: **27W**
- Tension: **220V-240V**
- Flux Lumineux (lm): **2592lm**
- CCT: **4000K**
- Efficiency: **77%**
- Efficacy: **95.99lm/W**
- CRI: **80**

Remarques

Allows intallation and supplying of 1 to 4 PAD 230V projectors. MV through-wiring included. Upper screen in PMMA included for double emission version. PAD projectors to be ordered separately.

DESCRIPTION

A modular system for ceiling or wall-recessed installation, to be installed as a continuous line or with angles, composed of structural modules in extruded aluminium, of pre-wired gear plates with through-wiring and quick-connection system of optics systems and components for connecting, fixing, joining or finishing the system. The prewired LED plates were designed for diffused emission, wall washer light, prismoptic or controlled emission, for projectors integration (PAD or Cube 37), for 3 phase track alimantation. Complies with standard EN60598-1 and any other specific standard.

CARACTÉRISTIQUES

- Code Produit : **M2945N00**
- Installation: **ProjecteurEncastréPlafonnier**
- Séries: **Architectural Indoor**
- dessiné par: **Carlotta de Bevilacqua, Paola di Arianello**

DIMENSIONS

- Longueur : **1180 mm**
- Poids: **kg 1,2**
- Test au fil incandescent: **650°**

ACCESSOIRES

NO
IMAGE
AVAILABLE

Algoritmo System - Embout intermédiaire (jeu 2 pièces). Pour la liaison esthétique de modules à projecteur PAD ou 37 CUBE avec des modules fluorescents ou LED. Gris métallisé. M217660

NO
IMAGE
AVAILABLE

ALGORTIMO - PAS pour ALGORITMO - Plaque de fermeture. Vient obturer les positions où aucun spot PAD n'a été installé. 1 pièce requise par emplacement vide. gris-métallisé M217760