

Algoritmo System for projectors - Pre-wired gear tray for Rail - Direct rail + indirect emission 4000K non dimmable

Carlotta de Bevilacqua
Paola di Arianello



LUMINAIRE

- Watt: **27W**
- Flux Lumineux (lm): **2592lm**
- CCT: **4000K**
- Efficiency: **77%**
- Efficacy: **95.99lm/W**
- CRI: **80**

Remarques

Double emission version, with upper screen in PMMA.

DESCRIPTION

A modular system for ceiling or wall-recessed installation, to be installed as a continuous line or with angles, composed of structural modules in extruded aluminium, of pre-wired gear plates with through-wiring and quick-connection system of optics systems and components for connecting, fixing, joining or finishing the system. The prewired LED plates were designed for diffused emission, wall washer light, prismoptic or controlled emission, for projectors integration (PAD or Cube 37), for 3 phase track alimentation. Complies with standard EN60598-1 and any other specific standard.

CARACTÉRISTIQUES

- Code Produit : **M2943N10**
- Couleur: **Black**
- Installation: **ProjecteurRail**
- Séries: **Architectural Indoor**
- dessiné par: **Carlotta de Bevilacqua, Paola di Arianello**

DIMENSIONS

- Longueur : **1180 mm**
- Poids: **kg 6**
- Test au fil incandescent: **650°**