


Antartikós - White Light

Carlotta de Bevilacqua



IP65    Dimmerable: 



LUMINAIRE

- Watt: **3W**
- Delivered lumens output: **20lm**
- CCT: **3000K**
- CRI: **80**
- Dimmable Typology: **Push/DALI**

Notes

Driver 500/700mA supplied separately. Depending on the driver, the device can be dimmable or non-dimmable. N° device per driver: 1-5 DV3003, 1-4 NL19035, 1-9 DV1003, 1-12 DV1042

DESCRIPTION

An innovative patented optic realizes a light blade that, from a single LED source, draws a 360 ° light profile. A perfect tool for architectural lighting that emphasizes with high efficiency the different opening profiles

PRODUCT CODE: T4520030

FEATURES

- Article Code: **T4520030**
- Colour: **Aluminium**
- Installation: **CeilingWallFloor**
- Series: **Architectural Outdoor**
- Environment: **Outdoor**
- design by: **Carlotta de Bevilacqua**

DIMENSIONS

- Length: **cm 11.7**
- Width: **cm 5.2**
- Height: **cm 8.1**
- Impact Resistance: **IK06**

Accessories

NO
IMAGE
AVAILABLE

Driver 25W - 220-240Vac - 164x38x25 (LxWxH) -
Dimmable DALI/PUSH
DV1003

NO
IMAGE
AVAILABLE

Driver 14W - 700mA 220-240 - 79x38x25
(LxWxH) - IP67 - Undimable
DV3003

NO
IMAGE
AVAILABLE

Driver 38W - 220-240 - 185x35x33 (LxWxH) - IP67 -
Dimmable DALI
DV1042

NO
IMAGE
AVAILABLE

Driver 10W - 700mA 220-240 Vac - 75x38x25
(LxWxH) - IP20 - Undimable
NL19035