



Everything 105 - Round - Trimless - 28° 3000K - Polished metal

Ernesto Gismondi



IP 20/44 



LUMINAIRE

- Watt: **13W**
- Flux Lumineux (lm): **833lm**
- CCT: **3000K**
- Efficiency: **60%**
- Efficacy: **64.05lm/W**
- CRI: **90**

Remarques

Driver 350mA SELV supplied separately.
Fitting to be completed with installation frame for recessing into ceiling.
APP Compatible version on request.
Geo-LiFi Compatible

DESCRIPTION

Everything is an innovative range of professional recessed light fittings created to deliver a high lighting performance, with an eye on energy saving and excellent visual comfort. A complete, flexible product range, extremely versatile in its many applications and able to meet challenging lighting performance criteria.
APP Compatible version on request.

CARACTÉRISTIQUES

- Code Produit : **M257800**
- Couleur: **Polished Metal**
- Installation: **Encastré**
- Matériaux: **aluminium**
- Séries: **Architectural Indoor**
- dessiné par: **Ernesto Gismondi**

DIMENSIONS

- Diamètre: **80 mm**
- Profondeur de la découpe: **130 mm**
- Rotation: **360°**
- Forme de la découpe: **Rond**
- Poids: **kg 0,3**
- Test au fil incandescent: **850°**
- Trou d'encastrement: **Thickness 1mm - 25mm**

SOURCES INCLUES

- Catégorie: **Led**
- Nombre: **1**
- Watt: **13W**
- Température de Couleur (K): **3000K**
- CRI: **90**
- Color Tolerance: **MacAdam 3SDCM**
- Service Life: **L80 (9K) 50000h**

ACCESSOIRES



Cornice per incasso tondo M273400

NO
IMAGE
AVAILABLE

DRIVER cc 15W 350mA 220-240 125 38 23 1max
Non dimmable M077500

NO
IMAGE
AVAILABLE

Driver 16/20/23/25/28/32W - 900mA - 220-240
156x52x26 (LxWxH) Dimmable DALI/PUSH
M077401



Power Kit Geo-LiFi - CC Mod=50% - 230x80x25h -
Undimmable VLCcoding - The nominal flux for this
application is halved DV1060