

Sharp - 16 optic unit - 44W - 20° 3000K Trim Black

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.



IP20  

PRODUCT CODE: AF25004

FEATURES


- Article Code: **AF25004**
- Colour: **Black**
- Installation: **Recessed**
- Series: **Architectural Indoor**
- Environment: **Indoor**
- design by: **Carlotta de Bevilacqua**

DIMENSIONS

- Length: **cm 60.8**
- Width: **cm 5.5**
- Height: **cm 5.5**

SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **44W**
- Color Tolerance: **MacAdam 2SDCM**
- Service Life: **L90 (17K) 103000h**



LUMINAIRE

- Watt: **44W**
- Delivered lumens output: **3215lm**
- CCT: **3000K**
- Efficiency: **76%**
- Efficacy: **73.08lm/W**
- CRI: **90**

Notes

Driver 900mA SELV and louvres supplied separately. (Required for installation)

Accessories



Louvres 4x White AF95201



Louvres 4x Black AF95204

NO
IMAGE
AVAILABLE

Driver 50W 1050mA - 220-240Vac - 124x79x22
(LxWxH) - 12x/16x Optic Units - Min Ceiling depth
80mm - Undimmable DV1005

NO
IMAGE
AVAILABLE

Driver 40W 900mA - 220-240Vac - 97x43x30
(LxWxH) - 8x/16x Optic Units - Min Ceiling depth
80mm - Undimmable DV1006

NO
IMAGE
AVAILABLE

Driver 48W 900mA - 220-240Vac - 110x75x26
(LxWxH) - 12x/16x Optic Units - Min Ceiling depth
80/80mm - DALI DV1007



Sharping wall grazer lens Kit (4pcs) - 26°x70°
elliptical lenses kit. It has to be used on top of S 20°
reflectors to get an elliptical beam (greter axis along
the module lenght). It contains 4 lenses. AF06000

NO
IMAGE
AVAILABLE

Driver 48W - 900mA - 220-240 125x82x29
(LxWxH) Dimmable DALI PUSH/1-10V/0-10V
DV1063