

Vector Magnetic 55 - 22° 2700K DALI Brushed copper

Carlotta de Bevilacqua



IP20   Dimmerable: 



LUMINAIRE

- Watt: **26W**
- Delivered lumens output: **1408lm**
- CCT: **2700K**
- Efficiency: **62%**
- Efficacy: **54.16lm/W**
- CRI: **90**
- Dimmable Typology: **Dali**

Notes

For operation use only Artemide Power Supply kit.

DESCRIPTION

Four sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom.

PRODUCT CODE: AP11218

FEATURES

- Article Code: **AP11218**
- Colour: **Brushed Copper**
- Installation: **ProjectorTrack**
- Series: **Architectural Indoor**
- Environment: **Indoor**
- design by: **Carlotta de Bevilacqua**

DIMENSIONS

- Height: **cm 15.5**
- Diameter: **cm 5.5**
- Base Length: **cm 24.8**
- Inclination: **-90+90**
- Rotation: **360°**
- Weight: **cm 0.5**

SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **26W**
- Color temperature (K): **2700K**
- CRI: **90**
- Color Tolerance: **MacAdam 3SDCM**
- Service Life: **L70 (6K) 50000h**

Accessories



Accessories holder - Vector 55
AP91100



Lens for elliptical emission - Vector 55
AP91200



Soft filter - Vector 55
AP91300



Anti-dazzle louvre - Vector 55
AP91400



Adjustable dowsers - Vector 55
AP91500