


# Vector Track 55 16° 2700K DALI

## Brushed silver

Carlotta de Bevilacqua



IP20    Dimmerable: 



### LUMINAIRE

- Watt: **25W**
- Delivered lumens output: **1434lm**
- CCT: **2700K**
- Efficiency: **64%**
- Efficacy: **57.35lm/W**
- CRI: **90**
- Dimmable Typology: **Dali**

### Notes

220/240Vac 50/60Hz Electronic ballast included.

### DESCRIPTION

Three sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Vector 55 track DALI zoom optic (22°-32°). Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 95 available only in track version. Version with compact 4-conductor (3p+n) adapter with hidden LED driver and not-dimmable phase selector.

**PRODUCT CODE: AN11615**

### FEATURES

- Article Code: **AN11615**
- Colour: **Brushed Silver**
- Installation: **ProjectorTrack**
- Series: **Architectural Indoor**
- Environment: **Indoor**
- design by: **Carlotta de Bevilacqua**

### DIMENSIONS

- Height: **cm 18.1**
- Diameter: **cm 5.5**
- Base Length: **cm 25.3**
- Inclination: **-90+90**
- Rotation: **360°**

### SOURCES INCLUDED

- Category: **Led**
- Number: **1**
- Watt: **25W**
- Color temperature (K): **2700K**

**Accessories**



Accessories holder - Vector 55 AP91100



Lens for elliptical emission - Vector 55 AP91200



Soft filter - Vector 55 AP91300



Anti-dazzle louvre - Vector 55 AP91400



Adjustable dowsers - Vector 55 AP91500