# Vector Track 55 22° 3000K Undimmable Black


## Carlotta de Bevilacqua



#### **DESCRIPTION**

Three sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. Vector 55 track DALI zoom optic (22°-32°). Junction arm integrated in the spotlight's body to keep the barycentre aligned with the track and prevent any imbalance in possible suspension versions of the track. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 95 available only in track version. Version with compact 4-conductor (3p+n) adapter with hidden LED driver and not-dimmable phase selector.

### IP20 🔲 🌃 C €



#### LUMINAIRE

- Watt: **25W** 

- Delivered lumens output: 1466lm

CCT: 3000KEfficiency: 62%Efficacy: 58.62lm/W

- CRI: 90

#### Notes

220/240Vac 50/60Hz Electronic ballast included

#### **PRODUCT CODE: AN10204**

#### **FEATURES**

- Article Code: AN10204

- Colour: Black

Installation: ProjectorTrackSeries: Architectural Indoor

- Environment: Indoor

- design by: Carlotta de Bevilacqua

#### **DIMENSIONS**

Height: cm 18.1
Diameter: cm 5.5
Base Length: cm 16.2
Inclination: -90+90
Rotation: 360°

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 26W

- Color temperature (K): 3000K

- CRI: 90

Color Tolerance: MacAdam 3SDCMService Life: L80 (9K) > 50000h



#### **Accessories**



Accessories holder - Vector 55 AP91100



Lens for elliptical emission - Vector 55 AP91200



Soft filter - Vector 55 AP91300



Anti-dazzle louvre - Vector 55 AP91400



Adjustable dowsers - Vector 55 AP91500

