

## Luminaire

Code M248341  
Name TAGORA 570 SOFFITTO LED DIMMERABILE DALI 4000K NERO/VERDE

## Measurem.

Code FTS2200129-A  
Name TAGORA 570 SOFFITTO LED DIMMERABILE DALI 4000K NERO/VERDE

Luminaire Flux	3432 lm	Luminaire Power	54.0 W	Efficacy	63.556 lm/W	Efficiency	100.00%
Source Flux	3432 lm	Maximum value	420.43 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	570 mm	Height	195 mm		
Round Luminous Area		Diam.	475 mm	Height	0 mm		
Horizontal Luminous Area		0.177205 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.042870 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		27-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3432 lm	
LED Flux=8528lm LED Power=50W Eff=40% EfcLed=172lm/W EfcLum=64lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(11k)=69000h							
C.I.E.	55 88 99 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 3		


Diam=570mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
DLOR100.00 %  
RN 0.00 %



## Luminaire

Code M248341  
Name TAGORA 570 SOFFITTO LED DIMMERABILE DALI 4000K NERO/VERDE

## Measurem.


Code FTS2200129-A  
Name TAGORA 570 SOFFITTO LED DIMMERABILE DALI 4000K NERO/VERDE

Luminaire Flux	3432 lm	Luminaire Power	54.0 W	Efficacy	63.556 lm/W	Efficiency	100.00%
Source Flux	3432 lm	Maximum value	420.43 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Round Luminaire		Diam.	570 mm	Height	195 mm		
Round Luminous Area		Diam.	475 mm	Height	0 mm		
Horizontal Luminous Area		0.177205 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.042870 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		27-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3432 lm	
LED Flux=8528lm LED Power=50W Eff=40% EfcLed=172lm/W EfcLum=64lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(11k)=69000h							
C.I.E.	55 88 99 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 3		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.23	2.46	3.69	4.92	6.15	OC	1.23	2.46	3.69	4.92	6.15
OB	1.23	2.46	3.69	4.92	6.15	OD	1.23	2.46	3.69	4.92	6.15

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1442.91	1436.20	1383.48	1274.64	1103.29	875.45	608.90	326.94	70.96	4.24
OB	1442.91	1436.20	1383.48	1274.64	1103.29	875.45	608.90	326.94	70.96	4.24
OC	1442.91	1436.20	1383.48	1274.64	1103.29	875.45	608.90	326.94	70.96	4.24
OD	1442.91	1436.20	1383.48	1274.64	1103.29	875.45	608.90	326.94	70.96	4.24



H[m]	D[m]	Max lux	Med lux	Alpha=50.9°+50.9°	G=0.0
1.00	2.46	1443	440		
2.00	4.92	361	110		
3.00	7.38	160	49		
4.00	9.84	90	27		
5.00	12.30	58	18		