

Luminaire

Code AF05505+AF95104

Name SHARP RECESSED TRIM 2X 6W 930 VERY WIDE FLOOD SILVER EXT.DRV + SCREEN 2X BLACK

Measurem.

Code FTS1603232-C

Name SHARP RECESSED TRIM 2X 6W 930 VERY WIDE FLOOD SILVER EXT.DRV + SCREEN 2X BLACK

Luminaire Flux	380 lm	Luminaire Power	5.5 W	Efficacy	69.122 lm/W	Efficiency	100.00%
Source Flux	380 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Rectangular Luminaire		Length	74 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	72 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.002664 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000644 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		380 lm	
LED Flux=530.66lm LED Power=5.5W Eff=72% EfcLed=96lm/W EfcLum=69lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	

74mm x 40mm



Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



