

Luminaire


Code BH12104+BH16004
Name A.39 SHARP D+IND 1184 LB 17 400K ND NRO + COVER 2X4 OPT. LB BLACK

Measurem.

Code FTS1900055-A
Name A.39 SHARP D+IND 1184 LB 17 400K ND NRO + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4811 lm	Luminaire Power	53.0 W	Efficacy	90.774 lm/W	Efficiency	100.00%
Source Flux	4811 lm	Maximum value	2022.20 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4811 lm	
LED Flux=6037lm LED Power=42W Eff=80% EfcLed=144lm/W EfcLum=91lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	100	100	100	36	100	D DIN 5040	D62
F UTE	--					B NBN	BZ 1

1184mm x 40mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 63.91 %

DLOR 36.09 %

RN 63.91 %

