

Luminaire

Code BH12304+BH16001
Name A.39 SHARP D+IND 1184 LB 17 400K DM NRO + COVER 2X4 OPT. LB WHITE

Measurem.

Code FTS1900343-A
Name A.39 SHARP D+IND 1184 LB 17 400K DM NRO + COVER 2X4 OPT. LB WHITE

| | | | | | | | |
|--|-------------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 4839 lm | Luminaire Power | 53.0 W | Efficacy | 91.302 lm/W | Efficiency | 100.00% |
| Source Flux | 4839 lm | Maximum value | 2020.16 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.002650 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 03-03-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4839 lm | |
| LED Flux=6037lm LED Power=42W Eff=80% EfcLed=144lm/W EfcLum=91lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h | | | | | | | |
| C.I.E. | 99 100 100 36 100 | | | D DIN 5040 | | D62 | |
| F UTE | -- | | | B NBN | | BZ 1 | |

1184mm x 40mm




Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 63.54 %

DLOR 36.46 %

RN 63.54 %



Luminaire

Code BH12304+BH16001
Name A.39 SHARP D+IND 1184 LB 17 400K DM NRO + COVER 2X4 OPT. LB WHITE

Measurem.


Code FTS1900343-A
Name A.39 SHARP D+IND 1184 LB 17 400K DM NRO + COVER 2X4 OPT. LB WHITE

| | | | | | | | |
|--|---------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 4839 lm | Luminaire Power | 53.0 W | Efficacy | 91.302 lm/W | Efficiency | 100.00% |
| Source Flux | 4839 lm | Maximum value | 2020.16 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.002650 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 03-03-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4839 lm | |
| LED Flux=6037lm LED Power=42W Eff=80% EfcLed=144lm/W EfcLum=91lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 36 | 100 | D DIN 5040 | D62 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| | | | | | | | | | | | |
|------|------|------|------|------|------|------|------|------|------|------|------|
| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
| OA | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 | OC | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 |
| OB | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 | OD | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 |

| | | | | | | | | | | |
|----|--------------------------------|---------|---------|--------|-------|-------|------|------|------|------|
| | Luminous Intensities [cd/klm] | | | | | | | | | |
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 9775.55 | 8319.03 | 2566.52 | 701.73 | 44.03 | 12.42 | 4.32 | 2.77 | 1.96 | 0.92 |
| OB | 9775.55 | 8319.03 | 2566.52 | 701.73 | 44.03 | 12.42 | 4.32 | 2.77 | 1.96 | 0.92 |
| OC | 9775.55 | 8319.03 | 2566.52 | 701.73 | 44.03 | 12.42 | 4.32 | 2.77 | 1.96 | 0.92 |
| OD | 9775.55 | 8319.03 | 2566.52 | 701.73 | 44.03 | 12.42 | 4.32 | 2.77 | 1.96 | 0.92 |



| H[m] | D[m] | Max lux | Med lux | Alpha=10.0°+10.0° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.35 | 9776 | 6233 | | |
| 2.00 | 0.70 | 2444 | 1558 | | |
| 3.00 | 1.05 | 1086 | 693 | | |
| 4.00 | 1.41 | 611 | 390 | | |
| 5.00 | 1.76 | 391 | 249 | | |

| H[m] | D[m] | Max lux | Med lux | Beta=10.0°+10.0° | G=0.0 |
|------|------|---------|---------|------------------|-------|
| 1.00 | 0.35 | 9776 | 6233 | | |
| 2.00 | 0.70 | 2444 | 1558 | | |
| 3.00 | 1.05 | 1086 | 693 | | |
| 4.00 | 1.41 | 611 | 390 | | |
| 5.00 | 1.76 | 391 | 249 | | |