

Luminaire


Code AF55600+AF95101
Name SHARP RECESSED TRIMLESS 2X 6W 940 FLOOD EXT.DRV + SCREEN 2X WHITE

Measurem.

Code FTS1603188-B
Name SHARP RECESSED TRIMLESS 2X 6W 940 FLOOD EXT.DRV + SCREEN 2X WHITE

Luminaire Flux	430 lm	Luminaire Power	5.5 W	Efficacy	78.216 lm/W	Efficiency	100.00%
Source Flux	430 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Rectangular Luminaire		Length	74 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	72 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.002664 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000644 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		430 lm	
LED Flux=567.99lm LED Power=5.5W Eff=76% EfcLed=103lm/W EfcLum=78lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	

74mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

