

Luminaire


Code AF36705+AF95104
Name SHARP SMD.2X 5,5W 940 WF EXD SIL+ SCREEN 2X BLACK

Measurem.

Code FTS1902099
Name SHARP SMD.2X 5,5W 940 WF EXD SIL+ SCREEN 2X BLACK

| | | | | | | | |
|--|--------|-----------------|----------------|-----------------------------|---------------|--------------------|---------|
| Luminaire Flux | 398 lm | Luminaire Power | 6.5 W | Efficacy | 61.169 lm/W | Efficiency | 100.00% |
| Source Flux | 398 lm | Maximum value | 2630.91 cd/klm | Position | C=0.00 G=0.00 | CG Rotosymmetrical | |
| Rectangular Luminaire | | Length | 78 mm | Width | 45 mm | Height | 90 mm |
| Rectangular Luminous Area | | Length | 72 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.002664 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000644 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 16-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 398 lm | |
| LED Flux=567.99lm LED Power=6.5W Eff=70% EfcLed=87lm/W EfcLum=61lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 100 | D DIN 5040 | A60 | |
| F UTE | -- | | | | B NBN | BZ 1 | |


78mm x 45mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code AF36705+AF95104
Name SHARP SMD.2X 5,5W 940 WF EXD SIL+ SCREEN 2X BLACK

Measurem.


Code FTS1902099
Name SHARP SMD.2X 5,5W 940 WF EXD SIL+ SCREEN 2X BLACK

| | | | | | | | |
|--|--------|-----------------|----------------|-----------------------------|---------------|--------------------|---------|
| Luminaire Flux | 398 lm | Luminaire Power | 6.5 W | Efficacy | 61.169 lm/W | Efficiency | 100.00% |
| Source Flux | 398 lm | Maximum value | 2630.91 cd/klm | Position | C=0.00 G=0.00 | CG Rotosymmetrical | |
| Rectangular Luminaire | | Length | 78 mm | Width | 45 mm | Height | 90 mm |
| Rectangular Luminous Area | | Length | 72 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.002664 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000644 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 16-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 398 lm | |
| LED Flux=567.99lm LED Power=6.5W Eff=70% EfcLed=87lm/W EfcLum=61lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| | | | | | | | | | | | |
|------|------|------|------|------|------|------|------|------|------|------|------|
| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
| OA | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 | OC | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 |
| OB | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 | OD | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 |

| | | | | | | | | | | |
|----|--------------------------------|--------|--------|--------|-------|------|------|------|------|------|
| | Luminous Intensities [cd/klm] | | | | | | | | | |
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 1046.05 | 971.73 | 638.97 | 227.79 | 38.73 | 7.80 | 0.92 | 0.13 | 0.00 | 0.00 |
| OB | 1046.05 | 971.73 | 638.97 | 227.79 | 38.73 | 7.80 | 0.92 | 0.13 | 0.00 | 0.00 |
| OC | 1046.05 | 971.73 | 638.97 | 227.79 | 38.73 | 7.80 | 0.92 | 0.13 | 0.00 | 0.00 |
| OD | 1046.05 | 971.73 | 638.97 | 227.79 | 38.73 | 7.80 | 0.92 | 0.13 | 0.00 | 0.00 |



| H[m] | D[m] | Max lux | Med lux | Alpha=18.0°+18.0° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.65 | 1046 | 608 | | |
| 2.00 | 1.30 | 262 | 152 | | |
| 3.00 | 1.95 | 116 | 68 | | |
| 4.00 | 2.60 | 65 | 38 | | |
| 5.00 | 3.25 | 42 | 24 | | |