

## Luminaire


Code BZ05604+BZ06204  
Name A.39 S SHARP REFR.D+I 2960 840 DALINRO + KIT LOUVRES 2960 NRO

## Measurerm.

Code FTS2102211-B  
Name A.39 S SHARP REFR.D+I 2960 840 DALINRO + KIT LOUVRES 2960 NRO

Luminaire Flux	20002 lm	Luminaire Power	153.0 W	Efficacy	130.732 lm/W	Efficiency	100.00%
Source Flux	20002 lm	Maximum value	690.66 cd/klm	Position	C=5.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2950 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.103250 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.024978 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		22-01-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		20002 lm	
LED Flux=24556lm LED Power=132W Eff=81% EfcLed=186lm/W EfcLum=131lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6k)=50000h							
C.I.E.	98 100 100 59 100			D DIN 5040	C61		
F UTE	--			B NBN	BZ 1		

2960mm x 45mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 40.99 %

DLOR 59.01 %

RN 40.99 %

