

Luminaire

Code FU82001
Name SHARPING 8 PENDANT FUNIVIA 940 FL BCO

Measurement

Code FTS2200027
Name SHARPING 8 PENDANT FUNIVIA 940 FL BCO

Luminaire Flux	1498 lm	Luminaire Power	19.0 W	Efficacy	78.842 lm/W	Efficiency	100.00%
Source Flux	1498 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	315 mm	Width	28 mm	Height	20 mm
Rectangular Luminous Area		Length	160 mm	Width	20 mm	Height	0 mm
Horizontal Luminous Area		0.003200 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000774 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1498 lm	
LED Flux=1840lm LED Power=16W Eff=81% EfcLed=116lm/W EfcLum=79lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(18k)=109000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

315mm x 28mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code FU82001
Name SHARPING 8 PENDANT FUNIVIA 940 FL BCO

Measurem.


Code FTS2200027
Name SHARPING 8 PENDANT FUNIVIA 940 FL BCO

Luminaire Flux	1498 lm	Luminaire Power	19.0 W	Efficacy	78.842 lm/W	Efficiency	100.00%
Source Flux	1498 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	315 mm	Width	28 mm	Height	20 mm
Rectangular Luminous Area		Length	160 mm	Width	20 mm	Height	0 mm
Horizontal Luminous Area		0.003200 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000774 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1498 lm	
LED Flux=1840lm LED Power=16W Eff=81% EfcLed=116lm/W EfcLum=79lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(18k)=109000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.24	0.47	0.71	0.95	1.18	OC	0.25	0.50	0.75	1.00	1.25
OB	0.24	0.47	0.71	0.95	1.18	OD	0.25	0.50	0.75	1.00	1.25

				Luminous Intensities [cd/klm]							
	0	5	15	25	35	45	55	65	75	85	
OA	4170.65	3785.94	1753.91	701.97	398.11	9.98	3.46	0.99	0.00	0.00	
OB	4170.65	3785.94	1753.91	701.97	398.11	9.98	3.46	0.99	0.00	0.00	
OC	4170.65	3941.03	1912.86	758.92	393.26	14.55	4.00	0.95	0.00	0.00	
OD	4170.65	3941.03	1912.86	758.92	393.26	14.55	4.00	0.95	0.00	0.00	



H[m]	D[m]	Max lux	Med lux	Alpha=13.3°+13.3°	G=0.0 Max non a G
1.00	0.47	4214	2600		
2.00	0.95	1054	650		
3.00	1.42	468	289		
4.00	1.89	263	163		
5.00	2.37	169	104		

H[m]	D[m]	Max lux	Med lux	Beta=14.1°+14.1°	G=0.0 Max non a G
1.00	0.50	4214	2600		
2.00	1.00	1054	650		
3.00	1.50	468	289		
4.00	2.01	263	163		
5.00	2.51	169	104		