

## Luminaire


Code TT32000  
Name SOMNIUM S SYS. D+I 2100mm 4000K ALU

## Measurement

Code FTS2500061  
Name SOMNIUM S SYS. D+I 2100mm 4000K ALU

Luminaire Flux	3710 lm	Luminaire Power	24.0 W	Efficacy	154.583 lm/W	Efficiency	100.00%
Source Flux	3710 lm	Maximum value	445.93 cd/klm	Position	C=10.00 G=4.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2100 mm	Width	30 mm	Height	32 mm
Rectangular Luminous Area		Length	1260 mm	Width	30 mm	Height	18 mm
Horizontal Luminous Area		0.037800 m <sup>2</sup>		Emitting area on Plane 180°		0.022680 m <sup>2</sup>	
Emitting area on Plane 0°		0.022680 m <sup>2</sup>		Emitting area on Plane 270°		0.000540 m <sup>2</sup>	
Emitting area on Plane 90°		0.000540 m <sup>2</sup>		Glare area at 76°		0.031151 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3710 lm	
LED Flux=4007lm LED Power=24W Eff=93% EfcLed=167lm/W EfcLum=155lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	94 98 99 52 100			D DIN 5040		C61	
F UTE	0.52 A + 0.48 T			B NBN		BZ 1	

2100mm x 30mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 48.06 %

DLOR 51.94 %

RN 48.06 %

