

Luminaire


Code 1860000APP
Name DREISPITZ F DIF SIL APP

Measurement

Code FTS2500137
Name DREISPITZ F DIF SIL APP

Luminaire Flux	6723 lm	Luminaire Power	52.0 W	Efficacy	129.288 lm/W	Efficiency	100.00%
Source Flux	6723 lm	Maximum value	115.78 cd/klm	Position	C=90.00 G=177.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1846 mm	Width	99 mm	Height	104 mm
Rectangular Luminous Area		Length	1500 mm	Width	90 mm	Height	60 mm
Horizontal Luminous Area		0.135000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°		0.090000 m2		Emitting area on Plane 270°		0.005400 m2	
Emitting area on Plane 90°		0.005400 m2		Glare area at 76°		0.119986 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		07-07-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6723 lm	
LED Flux=8305lm LED Power=49W Eff=81% EfcLed=171lm/W EfcLum=129lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	28 55 79 51 100			D DIN 5040		C11	
F UTE	0.51 J + 0.49 T			B NBN		BZ 7	

1846mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 48.80 %

DLOR 51.20 %

RN 48.80 %

