

Luminaire

Code AA00001_DM50

Name LOT RIFR.PROJ.LED R+W BCO - DMX - CH1 50 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Measurem.

Code FTS1700246

Name LOT RIFR.PROJ.LED R+W BCO - DMX - CH1 50 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	2090.40 lm	Luminaire Power	60.00 W	Efficacy	34.84 lm/W	Efficiency	100.00%
Lamps Flux	2090.40 lm	Maximum value	3662.85 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	185 mm	Height	80 mm		
Round Luminous Area		Diam.	105 mm	Height	0 mm		
Horizontal Luminous Area		0.008659 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002095 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-03-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2090.40 lm	
Continuous Power=60W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h							
C.I.E.	93 98 100 100 100			D DIN 5040		A60	
F UTE	1.00 A			B NBN		BZ 1	

Diam=185mm



Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



