

## Luminaire

Code AA00004\_DMX175

Name LOT RIFR.PROJ.LED R+W NRO - DMX - CH1 175 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

## Measurem.

Code FTS1700271

Name LOT RIFR.PROJ.LED R+W NRO - DMX - CH1 175 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	3788.02 lm	Luminaire Power	60.00 W	Efficacy	63.13 lm/W	Efficiency	100.00%
Lamps Flux	3788.02 lm	Maximum value	1843.06 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	185 mm	Height	80 mm		
Round Luminous Area		Diam.	180 mm	Height	0 mm		
Horizontal Luminous Area		0.025447 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006156 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-03-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3788.02 lm	
Continuous Power=60W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h							
C.I.E.	93 99 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=185mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



## Luminaire

Code AA00004\_DMX175

Name LOT RIFR.PROJ.LED R+W NRO - DMX - CH1 175 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

## Measurement

Code FTS1700271


Name LOT RIFR.PROJ.LED R+W NRO - DMX - CH1 175 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	3788.02 lm	Luminaire Power	60.00 W	Efficacy	63.13 lm/W	Efficiency	100.00%
Lamps Flux	3788.02 lm	Maximum value	1843.06 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	185 mm	Height	80 mm		
Round Luminous Area		Diam.	180 mm	Height	0 mm		
Horizontal Luminous Area		0.025447 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006156 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-03-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3788.02 lm	
Continuous Power=60W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h							
C.I.E.	93 99 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.35	0.70	1.04	1.39	1.74	OC	0.35	0.70	1.04	1.39	1.74
OB	0.35	0.70	1.04	1.39	1.74	OD	0.35	0.70	1.04	1.39	1.74

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	6981.54	6667.41	4544.47	2264.76	886.65	240.62	80.66	33.97	13.23	3.53
OB	6981.54	6667.41	4544.47	2264.76	886.65	240.62	80.66	33.97	13.23	3.53
OC	6981.54	6667.41	4544.47	2264.76	886.65	240.62	80.66	33.97	13.23	3.53
OD	6981.54	6667.41	4544.47	2264.76	886.65	240.62	80.66	33.97	13.23	3.53



H[m]	D[m]	Max lux	Med lux	Alpha=19.2°+19.2°	G=0.0
1.00	0.70	6982	4108		
2.00	1.39	1745	1027		
3.00	2.09	776	456		
4.00	2.79	436	257		
5.00	3.48	279	164		