

Luminaire

Code AN21620+M282100
Name VECTOR 95 TRACK 927 SP DALI BR.BRONZE + anti-dazzle louver

Measurem.

Code FTS2001573
Name VECTOR 95 TRACK 927 SP DALI BR.BRONZE + anti-dazzle louver

Luminaire Flux	1881.33 lm	Luminaire Power	30.00 W	Efficacy	62.71 lm/W	Efficiency	100.00%
Lamps Flux	1881.33 lm	Maximum value	8525.03 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	95 mm 74 mm	Height Height	210 mm 0 mm		
Horizontal Luminous Area		0.004301 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001040 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-03-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1881.33 lm	
LED Flux=3300lm LED Power=27.5W Eff=57% EfcLed=120lm/W EfcLum=63lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1



ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code AN21620+M282100
Name VECTOR 95 TRACK 927 SP DALI BR.BRONZE + anti-dazzle louver

Measurement


Code FTS2001573
Name VECTOR 95 TRACK 927 SP DALI BR.BRONZE + anti-dazzle louver

Luminaire Flux	1881.33 lm	Luminaire Power	30.00 W	Efficacy	62.71 lm/W	Efficiency	100.00%
Lamps Flux	1881.33 lm	Maximum value	8525.03 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Round Luminaire		Diam.	95 mm	Height	210 mm		
Round Luminous Area		Diam.	74 mm	Height	0 mm		
Horizontal Luminous Area		0.004301 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001040 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-03-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1881.33 lm	
LED Flux=3300lm LED Power=27.5W Eff=57% EfcLed=120lm/W EfcLum=63lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.13	0.26	0.39	0.53	0.66	OC	0.13	0.27	0.40	0.53	0.67
OB	0.13	0.26	0.39	0.53	0.66	OD	0.13	0.27	0.40	0.53	0.67

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	16038.40	11680.13	1971.83	736.55	28.38	8.12	3.18	1.50	1.00	0.45
OB	16038.40	11680.13	1971.83	736.55	28.38	8.12	3.18	1.50	1.00	0.45
OC	16038.40	11854.98	1935.02	735.16	29.61	10.23	4.77	2.30	1.27	0.51
OD	16038.40	11854.98	1935.02	735.16	29.61	10.23	4.77	2.30	1.27	0.51



H[m]	D[m]	Max lux	Med lux	Alpha=7.5°+7.5°	G=0.0
1.00	0.26	16038	10357		
2.00	0.53	4010	2589		
3.00	0.79	1782	1151		
4.00	1.05	1002	647		
5.00	1.32	642	414		

H[m]	D[m]	Max lux	Med lux	Beta=7.6°+7.6°	G=0.0
1.00	0.27	16038	10357		
2.00	0.53	4010	2589		
3.00	0.80	1782	1151		
4.00	1.06	1002	647		
5.00	1.33	642	414		