

Luminaire

Code BH12505+BH16004
Name A.39 SHARP D+IND 1184 LB 34 400K ND SIL + COVER 2X4 OPT. LB BLACK

Measurem.

Code FTS1900061-A
Name A.39 SHARP D+IND 1184 LB 34 400K ND SIL + COVER 2X4 OPT. LB BLACK

| | | | | | | | |
|--|---------|-----------------|---------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 4705 lm | Luminaire Power | 53.0 W | Efficacy | 88.774 lm/W | Efficiency | 100.00% |
| Source Flux | 4705 lm | Maximum value | 911.59 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.002650 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 03-03-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4705 lm | |
| LED Flux=6037lm LED Power=42W Eff=78% EfcLed=144lm/W EfcLum=89lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 35 | 100 | D DIN 5040 | D62 |
| F UTE | -- | | | | | B NBN | BZ 1 |

1184mm x 40mm




Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 65.35 %

DLOR 34.65 %

RN 65.35 %



Luminaire

Code BH12505+BH16004
Name A.39 SHARP D+IND 1184 LB 34 400K ND SIL + COVER 2X4 OPT. LB BLACK

Measurem.


Code FTS1900061-A
Name A.39 SHARP D+IND 1184 LB 34 400K ND SIL + COVER 2X4 OPT. LB BLACK

| | | | | | | | |
|--|---------|-----------------|---------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 4705 lm | Luminaire Power | 53.0 W | Efficacy | 88.774 lm/W | Efficiency | 100.00% |
| Source Flux | 4705 lm | Maximum value | 911.59 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.002650 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 03-03-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4705 lm | |
| LED Flux=6037lm LED Power=42W Eff=78% EfcLed=144lm/W EfcLum=89lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 35 | 100 | D DIN 5040 | D62 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| | | | | | | | | | | | |
|------|------|------|------|------|------|------|------|------|------|------|------|
| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
| OA | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 | OC | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 |
| OB | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 | OD | 0.33 | 0.65 | 0.98 | 1.30 | 1.63 |

| | | | | | | | | | | |
|----|--------------------------------|---------|---------|--------|--------|-------|------|------|------|------|
| | Luminous Intensities [cd/klm] | | | | | | | | | |
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 4289.02 | 3984.28 | 2619.93 | 934.00 | 158.79 | 31.99 | 3.76 | 0.52 | 0.00 | 0.00 |
| OB | 4289.02 | 3984.28 | 2619.93 | 934.00 | 158.79 | 31.99 | 3.76 | 0.52 | 0.00 | 0.00 |
| OC | 4289.02 | 3984.28 | 2619.93 | 934.00 | 158.79 | 31.99 | 3.76 | 0.52 | 0.00 | 0.00 |
| OD | 4289.02 | 3984.28 | 2619.93 | 934.00 | 158.79 | 31.99 | 3.76 | 0.52 | 0.00 | 0.00 |



| H[m] | D[m] | Max Lux | Med Lux | Alpha=18.0°+18.0° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.65 | 4289 | 2494 | | |
| 2.00 | 1.30 | 1072 | 624 | | |
| 3.00 | 1.95 | 477 | 277 | | |
| 4.00 | 2.60 | 268 | 156 | | |
| 5.00 | 3.25 | 172 | 100 | | |

| H[m] | D[m] | Max Lux | Med Lux | Beta=18.0°+18.0° | G=0.0 |
|------|------|---------|---------|------------------|-------|
| 1.00 | 0.65 | 4289 | 2494 | | |
| 2.00 | 1.30 | 1072 | 624 | | |
| 3.00 | 1.95 | 477 | 277 | | |
| 4.00 | 2.60 | 268 | 156 | | |
| 5.00 | 3.25 | 172 | 100 | | |