

## Luminaire


Code BH10501+BH16304  
Name A.39 SHARP D+IND 2368 HB 34 400K ND BCO + COVER 6X4 OPT. HB BLACK

## Measurem.

Code FTS1900277-B  
Name A.39 SHARP D+IND 2368 HB 34 400K ND BCO + COVER 6X4 OPT. HB BLACK

Luminaire Flux	11042 lm	Luminaire Power	125.0 W	Efficacy	88.336 lm/W	Efficiency	100.00%
Source Flux	11042 lm	Maximum value	1165.47 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		11042 lm	
LED Flux=14404lm LED Power=107W Eff=77% EfcLed=135lm/W EfcLum=88lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99	100	100	44	100	D DIN 5040	C62
F UTE	--					B NBN	BZ 1

2368mm x 40mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 55.70 %

DLOR 44.30 %

RN 55.70 %

