

Luminaire

Code BH10701+BH16304
Name A.39 SHARP D+IND 2368 HB 34 400K DM BCO + COVER 6X4 OPT. HB BLACK

Measurem.

Code FTS1900280-B
Name A.39 SHARP D+IND 2368 HB 34 400K DM BCO + COVER 6X4 OPT. HB BLACK

| | | | | | | | |
|--|----------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 11042 lm | Luminaire Power | 120.0 W | Efficacy | 92.017 lm/W | Efficiency | 100.00% |
| Source Flux | 11042 lm | Maximum value | 1165.47 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 2368 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 888 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.032856 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.007949 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 03-03-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 11042 lm | |
| LED Flux=14404lm LED Power=107W Eff=77% EfcLed=135lm/W EfcLum=92lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 44 | 100 | D DIN 5040 | C62 |
| F UTE | -- | | | | | B NBN | BZ 1 |

2368mm x 40mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 55.70 %

DLOR 44.30 %

RN 55.70 %



