

## Luminaire


Code BH10704+BH16304  
Name A.39 SHARP D+IND 2368 HB 34 400K DM NRO + COVER 6X4 OPT. HB BLACK

## Measurem.

Code FTS1900280-B  
Name A.39 SHARP D+IND 2368 HB 34 400K DM NRO + COVER 6X4 OPT. HB BLACK

|  |          |                 |                |                             |               |                    |                    |
|--|----------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux   | 11042 lm | Luminaire Power | 120.0 W        | Efficacy                    | 92.017 lm/W   | Efficiency         | 100.00%            |
| Source Flux  | 11042 lm | Maximum value   | 1165.47 cd/klm | Position                    | C=0.00 G=0.00 | CG                 | Double Symmetrical |
| Rectangular Luminaire  |          | Length          | 2368 mm        | Width                       | 40 mm         | Height             | 111 mm             |
| Rectangular Luminous Area  |          | Length          | 888 mm         | Width                       | 37 mm         | Height             | 0 mm               |
| Horizontal Luminous Area   |          | 0.032856 m2     |                | Emitting area on Plane 180° |               | 0.000000 m2        |                    |
| Emitting area on Plane 0°  |          | 0.000000 m2     |                | Emitting area on Plane 270° |               | 0.000000 m2        |                    |
| Emitting area on Plane 90°   |          | 0.000000 m2     |                | Glare area at 76°           |               | 0.007949 m2        |                    |
| Coordinate system  |          | CG              |                | Symmetry Type               |               | Double Symmetrical |                    |
| Date   |          | 03-03-2025      |                | Maximum Gamma Angle         |               | 180                |                    |
| Measurement Distance   |          | 0.00            |                | Measurement Flux            |               | 11042 lm           |                    |
| LED Flux=14404lm LED Power=107W Eff=77% EfcLed=135lm/W EfcLum=92lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h |          |                 |                |                             |               |                    |                    |
| C.I.E.   | 99       | 100             | 100            | 44                          | 100           | D DIN 5040         | C62                |
| F UTE  | --       |                 |                |                             |               | B NBN              | BZ 1               |

2368mm x 40mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 55.70 %

DLOR 44.30 %

RN 55.70 %

