

## Luminaire

Code BB10300\_50+M239600  
Name LUCERI Q TLESS 50W 930 COMFORT + schermo prismoptico


## Measurem.

Code FTS1801339-A  
Name LUCERI Q TLESS 50W 930 COMFORT + schermo prismoptico

Luminaire Flux	3498 lm	Luminaire Power	50.0 W	Efficacy	69.960 lm/W	Efficiency	100.00%
Source Flux	3498 lm	Maximum value	842.43 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	188 mm	Width	188 mm	Height	238 mm
Rectangular Luminous Area		Length	184 mm	Width	184 mm	Height	0 mm
Horizontal Luminous Area		0.033856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.008191 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3498 lm	
LED Flux=6047lm LED Power=50W Eff=58% EfcLed=121lm/W EfcLum=70lm/W CCT=3000K Ra=90 R9=50 SDCM=1 L70(9k)=50000h							
C.I.E.	76 94 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1 / 2.5 / BZ 2		



ULOR 0.04 %  
DLOR 99.96 %  
RN 0.04 %



## Luminaire

Code BB10300\_50+M239600  
Name LUCERI Q TLESS 50W 930 COMFORT + schermo prismoptico

## Measur.


Code FTS1801339-A  
Name LUCERI Q TLESS 50W 930 COMFORT + schermo prismoptico

Luminaire Flux	3498 lm	Luminaire Power	50.0 W	Efficacy	69.960 lm/W	Efficiency	100.00%
Source Flux	3498 lm	Maximum value	842.43 cd/klm	Position	C=0.00 G=0.00	CG Double Symmetrical	
Rectangular Luminaire		Length	188 mm	Width	188 mm	Height	238 mm
Rectangular Luminous Area		Length	184 mm	Width	184 mm	Height	0 mm
Horizontal Luminous Area		0.033856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.008191 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3498 lm	
LED Flux=6047lm LED Power=50W Eff=58% EfcLed=121lm/W EfcLum=70lm/W CCT=3000K Ra=90 R9=50 SDCM=1 L70(9k)=50000h							
C.I.E.	76 94 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1 / 2.5 / BZ 2		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.58	1.16	1.74	2.33	2.91	OC	0.58	1.16	1.74	2.33	2.91
OB	0.58	1.16	1.74	2.33	2.91	OD	0.58	1.16	1.74	2.33	2.91

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2946.81	2904.50	2512.44	1837.90	1123.32	519.88	251.93	136.74	56.88	13.47
OB	2946.81	2904.50	2512.44	1837.90	1123.32	519.88	251.93	136.74	56.88	13.47
OC	2946.81	2904.87	2526.93	1843.84	1105.94	506.53	250.81	138.28	56.54	12.92
OD	2946.81	2904.87	2526.93	1843.84	1105.94	506.53	250.81	138.28	56.54	12.92



H[m]	D[m]	Max lux	Med lux	Alpha=30.2°+30.2°	G=0.0
1.00	1.16	2947	1518		
2.00	2.33	737	379		
3.00	3.49	327	169		
4.00	4.65	184	95		
5.00	5.82	118	61		

H[m]	D[m]	Max lux	Med lux	Beta=30.2°+30.2°	G=0.0
1.00	1.16	2947	1518		
2.00	2.33	737	379		
3.00	3.49	327	169		
4.00	4.65	184	95		
5.00	5.81	118	61		