

Luminaire

Code BN01101
Name VECTOR 75L 3P DALI 927 SP WHT

Measurement

Code FTS2101981-A
Name VECTOR 75L 3P DALI 927 SP WHT

Luminaire Flux	1993 lm	Luminaire Power	20.0 W	Efficacy	99.650 lm/W	Efficiency	100.00%
Source Flux	1993 lm	Maximum value	10110.39 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	75 mm	Height	168 mm		
Round Luminous Area		Diam.	68 mm	Height	0 mm		
Horizontal Luminous Area		0.003632 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000879 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		30-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1993 lm	
LED Flux=2447lm LED Power=18W Eff=81% EfcLed=139lm/W EfcLum=100lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=75mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code BN01101
Name VECTOR 75L 3P DALI 927 SP WHT

Measurem.


Code FTS2101981-A
Name VECTOR 75L 3P DALI 927 SP WHT

Luminaire Flux	1993 lm	Luminaire Power	20.0 W	Efficacy	99.650 lm/W	Efficiency	100.00%
Source Flux	1993 lm	Maximum value	10110.39 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	75 mm	Height	168 mm		
Round Luminous Area		Diam.	68 mm	Height	0 mm		
Horizontal Luminous Area		0.003632 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000879 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		30-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1993 lm	
LED Flux=2447lm LED Power=18W Eff=81% EfcLed=139lm/W EfcLum=100lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.14	0.29	0.43	0.58	0.72	OC	0.14	0.29	0.43	0.58	0.72
OB	0.14	0.29	0.43	0.58	0.72	OD	0.14	0.29	0.43	0.58	0.72

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	20150.00	16252.70	1678.43	277.83	51.01	14.26	3.96	2.05	0.41	0.30
OB	20150.00	16252.70	1678.43	277.83	51.01	14.26	3.96	2.05	0.41	0.30
OC	20150.00	16252.70	1678.43	277.83	51.01	14.26	3.96	2.05	0.41	0.30
OD	20150.00	16252.70	1678.43	277.83	51.01	14.26	3.96	2.05	0.41	0.30



H[m]	D[m]	Max lux	Med lux	Alpha=8.2°+8.2°	G=0.0
1.00	0.29	20150	13131		
2.00	0.58	5037	3283		
3.00	0.87	2239	1459		
4.00	1.16	1259	821		
5.00	1.45	806	525		