

Luminaire

Code BN10320
Name VECTOR 75L 3P ND 930 WF BBZ

Measurement

Code FTS2101941-A
Name VECTOR 75L 3P ND 930 WF BBZ

Luminaire Flux	3539 lm	Luminaire Power	33.0 W	Efficacy	107.242 lm/W	Efficiency	100.00%
Source Flux	3539 lm	Maximum value	3040.61 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	75 mm	Height	168 mm		
Round Luminous Area		Diam.	68 mm	Height	0 mm		
Horizontal Luminous Area		0.003632 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000879 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		30-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3539 lm	
LED Flux=4428lm LED Power=29W Eff=80% EfcLed=151lm/W EfcLum=107lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


Diam=75mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code BN10320
Name VECTOR 75L 3P ND 930 WF BBZ

Measur.


Code FTS2101941-A
Name VECTOR 75L 3P ND 930 WF BBZ

Luminaire Flux	3539 lm	Luminaire Power	33.0 W	Efficacy	107.242 lm/W	Efficiency	100.00%
Source Flux	3539 lm	Maximum value	3040.61 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	75 mm	Height	168 mm		
Round Luminous Area		Diam.	68 mm	Height	0 mm		
Horizontal Luminous Area		0.003632 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000879 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		30-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3539 lm	
LED Flux=4428lm LED Power=29W Eff=80% EfcLed=151lm/W EfcLum=107lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.29	0.58	0.87	1.16	1.46	OC	0.29	0.58	0.87	1.16	1.46
OB	0.29	0.58	0.87	1.16	1.46	OD	0.29	0.58	0.87	1.16	1.46

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	10760.74	10044.43	5934.47	1814.53	167.76	24.78	9.05	6.26	3.22	0.57
OB	10760.74	10044.43	5934.47	1814.53	167.76	24.78	9.05	6.26	3.22	0.57
OC	10760.74	10044.43	5934.47	1814.53	167.76	24.78	9.05	6.26	3.22	0.57
OD	10760.74	10044.43	5934.47	1814.53	167.76	24.78	9.05	6.26	3.22	0.57



H[m]	D[m]	Max lux	Med lux	Alpha=16.2°+16.2°	G=0.0
1.00	0.58	10761	6492		
2.00	1.16	2690	1623		
3.00	1.75	1196	721		
4.00	2.33	673	406		
5.00	2.91	430	260		