

## Luminaire


Code TE22022\_indiretta  
Name TURN AROUND F D/I 3000K TIT. (solo indiretta)

## Measurem.

Code FTS2400489  
Name TURN AROUND F D/I 3000K TIT. (solo indiretta)

Luminaire Flux	6197 lm	Luminaire Power	53.0 W	Efficacy	116.928 lm/W	Efficiency	100.00%
Source Flux	6197 lm	Maximum value	441.36 cd/klm	Position	C=0.00 G=180.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1250 mm	Width	28 mm	Height	28 mm
Rectangular Luminous Area		Length	1130 mm	Width	23 mm	Height	0 mm
Horizontal Luminous Area		0.025990 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006288 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6197 lm	
LED Flux=8513lm LED Power=46W Eff=73% EfcLed=185lm/W EfcLum=117lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	0 0 0 0 100			D DIN 5040	--		
F UTE	1.00 T			B NBN	BZ 10		

1250mm x 28mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 99.99 %

DLOR 0.01 %

RN 99.99 %

