

Luminaire


Code CF30001+CF50004
Name HOY REFR TRACK 930 L=576 DALI BCO + HOY REFR KIT LOUVRE L=576 NRO

Measurem.

Code FTS2400521
Name HOY REFR TRACK 930 L=576 DALI BCO + HOY REFR KIT LOUVRE L=576 NRO

Luminaire Flux	1926 lm	Luminaire Power	16.0 W	Efficacy	120.375 lm/W	Efficiency	100.00%
Source Flux	1926 lm	Maximum value	1412.75 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	583 mm	Width	100 mm	Height	30 mm
Rectangular Luminous Area		Length	572 mm	Width	90 mm	Height	0 mm
Horizontal Luminous Area		0.051480 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.012454 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-12-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1926 lm	
LED Flux=2377lm LED Power=13W Eff=81% EfcLed=187lm/W EfcLum=120lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

583mm x 100mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

