

## Luminaire


Code CF02101+CF50104  
Name HOY REFR S D/I 940 L=1154 DALI BCO + HOY REFR KIT LOUVRE L=1154 NRO

## Measurem.

Code FTS2573  
Name HOY REFR S D/I 940 L=1154 DALI BCO + HOY REFR KIT LOUVRE L=1154 NRO

Luminaire Flux	3810 lm	Luminaire Power	29.0 W	Efficacy	131.379 lm/W	Efficiency	100.00%
Source Flux	3810 lm	Maximum value	734.56 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1154 mm	Width	100 mm	Height	58 mm
Rectangular Luminous Area		Length	1144 mm	Width	90 mm	Height	0 mm
Horizontal Luminous Area		0.102960 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.024908 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3810 lm	
LED Flux=4555lm LED Power=25W Eff=84% EfcLed=185lm/W EfcLum=131lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6k)=50000h							
C.I.E.	100	100	100	52	100	D DIN 5040	C61
F UTE	--					B NBN	BZ 1

1154mm x 100mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 48.00 %

DLOR 52.00 %

RN 48.00 %

