

Luminaire


Code 1852000A
Name DREISPITZ 120 S IND DIF SIL

Measurement

Code FTS2500029
Name DREISPITZ 120 S IND DIF SIL

Luminaire Flux	3287 lm	Luminaire Power	29.0 W	Efficacy	113.345 lm/W	Efficiency	100.00%
Source Flux	3287 lm	Maximum value	181.50 cd/klm	Position	C=35.00 G=178.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1132 mm	Width	99 mm	Height	74 mm
Rectangular Luminous Area		Length	1120 mm	Width	60 mm	Height	29 mm
Horizontal Luminous Area		0.067200 m2		Emitting area on Plane 180°		0.033600 m2	
Emitting area on Plane 0°		0.033600 m2		Emitting area on Plane 270°		0.001800 m2	
Emitting area on Plane 90°		0.001800 m2		Glare area at 76°		0.048859 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3287 lm	
LED Flux=4060lm LED Power=24W Eff=81% EfcLed=171lm/W EfcLum=113lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	17 40 69 31 100			D DIN 5040		D12	
F UTE	0.31 J + 0.69 T			B NBN		BZ 10	

1132mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 69.28 %

DLOR 30.72 %

RN 69.28 %

