

## Luminaire


Code 1213000A\_un-ottavo  
Name ALPHABET OF LIGHT S CIRCOLARE 350\_1/8

## Measurem.

Code FTS2400217  
Name ALPHABET OF LIGHT S CIRCOLARE 350\_1/8

Luminaire Flux	2619 lm	Luminaire Power	19.5 W	Efficacy	134.308 lm/W	Efficiency	100.00%
Source Flux	2619 lm	Maximum value	163.39 cd/klm	Position	C=25.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1366 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1366 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.068300 m2		Emitting area on Plane 180°		0.068300 m2	
Emitting area on Plane 0°		0.068300 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.082794 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		05-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2619 lm	
LED Flux=3312lm LED Power=18W Eff=79% EfcLed=188lm/W EfcLum=134lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 82 72 100			D DIN 5040	B21		
F UTE	0.72 H + 0.28 T			B NBN	BZ 6		

1366mm x 50mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 27.50 %

DLOR 72.50 %

RN 27.50 %

