

Luminaire


Code 1859000AAPP
Name DREISPITZ 120 S VERT DIF SIL APP

Measurem.

Code FTS2500035
Name DREISPITZ 120 S VERT DIF SIL APP

Luminaire Flux	4931 lm	Luminaire Power	40.0 W	Efficacy	123.275 lm/W	Efficiency	100.00%
Source Flux	4931 lm	Maximum value	115.78 cd/klm	Position	C=90.00 G=177.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1132 mm	Width	99 mm	Height	104 mm
Rectangular Luminous Area		Length	1120 mm	Width	90 mm	Height	60 mm
Horizontal Luminous Area		0.100800 m2		Emitting area on Plane 180°		0.067200 m2	
Emitting area on Plane 0°		0.067200 m2		Emitting area on Plane 270°		0.005400 m2	
Emitting area on Plane 90°		0.005400 m2		Glare area at 76°		0.089590 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4931 lm	
LED Flux=6090lm LED Power=36W Eff=81% EfcLed=171lm/W EfcLum=123lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	28 55 79 51 100			D DIN 5040		C11	
F UTE	0.51 J + 0.49 T			B NBN		BZ 7	

1132mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 48.80 %

DLOR 51.20 %

RN 48.80 %

