

Luminaire

Code AX11001
Name HELGOLAND 120 FIX 2700K FL BCO

Measurem.

Code FTS2600046
Name HELGOLAND 120 FIX 2700K FL BCO

Luminaire Flux	1176 lm	Luminaire Power	8.5 W	Efficacy	138.353 lm/W	Efficiency	100.00%
Source Flux	1176 lm	Maximum value	2961.35 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	120 mm	Height	12 mm		
Round Luminous Area		Diam.	89 mm	Height	0 mm		
Horizontal Luminous Area		0.006221 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001505 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		02-04-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1176 lm	
LED Flux=1458lm LED Power=8.5W Eff=81% EfcLed=171lm/W EfcLum=138lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	88 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=120mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AX11001
Name HELGOLAND 120 FIX 2700K FL BCO

Measurem.


Code FTS2600046
Name HELGOLAND 120 FIX 2700K FL BCO

Luminaire Flux	1176 lm	Luminaire Power	8.5 W	Efficacy	138.353 lm/W	Efficiency	100.00%
Source Flux	1176 lm	Maximum value	2961.35 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	120 mm	Height	12 mm		
Round Luminous Area		Diam.	89 mm	Height	0 mm		
Horizontal Luminous Area		0.006221 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001505 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		02-04-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1176 lm	
LED Flux=1458lm LED Power=8.5W Eff=81% EfcLed=171lm/W EfcLum=138lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	88 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.26	0.51	0.77	1.02	1.28	OC	0.26	0.51	0.77	1.02	1.28
OB	0.26	0.51	0.77	1.02	1.28	OD	0.26	0.51	0.77	1.02	1.28

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3482.55	3221.62	1630.51	450.40	126.79	66.65	50.40	30.99	14.50	3.43
OB	3482.55	3221.62	1630.51	450.40	126.79	66.65	50.40	30.99	14.50	3.43
OC	3482.55	3221.62	1630.51	450.40	126.79	66.65	50.40	30.99	14.50	3.43
OD	3482.55	3221.62	1630.51	450.40	126.79	66.65	50.40	30.99	14.50	3.43



H[m]	D[m]	Max lux	Med lux	Alpha=14.4°+14.4°	G=0.0
1.00	0.51	3483	2155		
2.00	1.02	871	539		
3.00	1.54	387	239		
4.00	2.05	218	135		
5.00	2.56	139	86		