

## Luminaire

Code AX92401  
Name HELGOLAND 90 FIX IP44 2700K XF BCO

## Measurement

Code FTS2600096.  
Name HELGOLAND 90 FIX IP44 2700K XF BCO

Luminaire Flux	840 lm	Luminaire Power	6.0 W	Efficacy	140.000 lm/W	Efficiency	100.00%
Source Flux	840 lm	Maximum value	1138.26 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	90 mm	Height	12 mm		
Round Luminous Area		Diam.	64 mm	Height	0 mm		
Horizontal Luminous Area		0.003217 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000778 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		03-04-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		840 lm	
LED Flux=1019lm LED Power=6W Eff=82% EfcLed=170lm/W EfcLum=140lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	91 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=90mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



## Luminaire

Code AX92401  
Name HELGOLAND 90 FIX IP44 2700K XF BCO

## Measurem.


Code FTS2600096.  
Name HELGOLAND 90 FIX IP44 2700K XF BCO

Luminaire Flux	840 lm	Luminaire Power	6.0 W	Efficacy	140.000 lm/W	Efficiency	100.00%
Source Flux	840 lm	Maximum value	1138.26 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	90 mm	Height	12 mm		
Round Luminous Area		Diam.	64 mm	Height	0 mm		
Horizontal Luminous Area		0.003217 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000778 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		03-04-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		840 lm	
LED Flux=1019lm LED Power=6W Eff=82% EfcLed=170lm/W EfcLum=140lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	91 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.57	1.14	1.70	2.27	2.84	OC	0.57	1.14	1.70	2.27	2.84
OB	0.57	1.14	1.70	2.27	2.84	OD	0.57	1.14	1.70	2.27	2.84

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	956.14	942.89	852.29	676.49	191.48	33.71	24.35	17.35	10.30	2.94
OB	956.14	942.89	852.29	676.49	191.48	33.71	24.35	17.35	10.30	2.94
OC	956.14	942.89	852.29	676.49	191.48	33.71	24.35	17.35	10.30	2.94
OD	956.14	942.89	852.29	676.49	191.48	33.71	24.35	17.35	10.30	2.94



H[m]	D[m]	Max lux	Med lux	Alpha=29.6°+29.6°	G=0.0
1.00	1.14	956	514		
2.00	2.27	239	128		
3.00	3.41	106	57		
4.00	4.54	60	32		
5.00	5.68	38	21		