

## Luminaire

Code NL4203125Y004  
Name Everything 35 square 24° - cornice nera - 2700K

## Measurement

Code FTS1602929-A  
Name Everything 35 square 24° - cornice nera - 2700K

Luminaire Flux	132 lm	Luminaire Power	1.4 W	Efficacy	94.286 lm/W	Efficiency	100.00%
Source Flux	132 lm	Maximum value	3699.96 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	34 mm	Height	48 mm		
Round Luminous Area		Diam.	22 mm	Height	0 mm		
Horizontal Luminous Area		0.000380 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000092 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		14-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		132 lm	
LED Flux=164lm LED Power=1.4W Eff=81% EfcLed=117lm/W EfcLum=94lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


Diam=34mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
DLOR100.00 %  
RN 0.00 %



## Luminaire

Code NL4203125Y004  
Name Everything 35 square 24° - cornice nera - 2700K

## Measurement


Code FTS1602929-A  
Name Everything 35 square 24° - cornice nera - 2700K

Luminaire Flux	132 lm	Luminaire Power	1.4 W	Efficacy	94.286 lm/W	Efficiency	100.00%
Source Flux	132 lm	Maximum value	3699.96 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Round Luminaire		Diam.	34 mm	Height	48 mm		
Round Luminous Area		Diam.	22 mm	Height	0 mm		
Horizontal Luminous Area		0.000380 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000092 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		14-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		132 lm	
LED Flux=164lm LED Power=1.4W Eff=81% EfcLed=117lm/W EfcLum=94lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.24	0.47	0.71	0.94	1.18	OC	0.24	0.47	0.71	0.94	1.18
OB	0.24	0.47	0.71	0.94	1.18	OD	0.24	0.47	0.71	0.94	1.18

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	488.39	439.44	204.38	55.90	11.86	2.53	0.69	0.16	0.11	0.10
OB	488.39	439.44	204.38	55.90	11.86	2.53	0.69	0.16	0.11	0.10
OC	488.39	439.44	204.38	55.90	11.86	2.53	0.69	0.16	0.11	0.10
OD	488.39	439.44	204.38	55.90	11.86	2.53	0.69	0.16	0.11	0.10



H[m]	D[m]	Max lux	Med lux	Alpha=13.3°+13.3°	G=0.0
1.00	0.47	488	301		
2.00	0.94	122	75		
3.00	1.41	54	33		
4.00	1.88	31	19		
5.00	2.36	20	12		