

Luminaire

Code NL4203418Y004
Name Everything 55 square 20° - cornice nera - 2700K

Measurement

Code FTS1602934-B
Name Everything 55 square 20° - cornice nera - 2700K

Luminaire Flux	511 lm	Luminaire Power	5.5 W	Efficacy	92.909 lm/W	Efficiency	100.00%
Source Flux	511 lm	Maximum value	8779.29 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	80 mm		
Round Luminous Area		Diam.	37 mm	Height	0 mm		
Horizontal Luminous Area		0.001075 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000260 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		511 lm	
LED Flux=640lm LED Power=5.5W Eff=80% EfcLed=116lm/W EfcLum=93lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


Diam=55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code NL4203418Y004
Name Everything 55 square 20° - cornice nera - 2700K

Measurem.


Code FTS1602934-B
Name Everything 55 square 20° - cornice nera - 2700K

Luminaire Flux	511 lm	Luminaire Power	5.5 W	Efficacy	92.909 lm/W	Efficiency	100.00%
Source Flux	511 lm	Maximum value	8779.29 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Round Luminaire		Diam.	55 mm	Height	80 mm		
Round Luminous Area		Diam.	37 mm	Height	0 mm		
Horizontal Luminous Area		0.001075 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000260 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		511 lm	
LED Flux=640lm LED Power=5.5W Eff=80% EfcLed=116lm/W EfcLum=93lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.16	0.32	0.48	0.64	0.80	OC	0.16	0.32	0.48	0.64	0.80
OB	0.16	0.32	0.48	0.64	0.80	OD	0.16	0.32	0.48	0.64	0.80

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4486.22	3678.13	606.00	36.92	7.91	3.52	1.96	0.27	0.18	0.14
OB	4486.22	3678.13	606.00	36.92	7.91	3.52	1.96	0.27	0.18	0.14
OC	4486.22	3678.13	606.00	36.92	7.91	3.52	1.96	0.27	0.18	0.14
OD	4486.22	3678.13	606.00	36.92	7.91	3.52	1.96	0.27	0.18	0.14



H[m]	D[m]	Max lux	Med lux	Alpha=9.1°+9.1°	G=0.0
1.00	0.32	4486	2869		
2.00	0.64	1122	717		
3.00	0.96	498	319		
4.00	1.28	280	179		
5.00	1.60	179	115		