

## Luminaire

Code BH10905+BH16301  
Name A.39 SHARP D+IND 2368 HB 54 400K ND SIL + COVER 6X4 OPT. HB WHITE

## Measurem.

Code FTS1900571-B  
Name A.39 SHARP D+IND 2368 HB 54 400K ND SIL + COVER 6X4 OPT. HB WHITE

Luminaire Flux	11278 lm	Luminaire Power	125.0 W	Efficacy	90.224 lm/W	Efficiency	100.00%
Source Flux	11278 lm	Maximum value	639.45 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		11278 lm	
LED Flux=14404lm LED Power=107W Eff=78% EfcLed=135lm/W EfcLum=90lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	97 99 100 45 100			D DIN 5040	C62		
F UTE	--			B NBN	BZ 1		

2368mm x 40mm




Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 54.53 %

DLOR 45.47 %

RN 54.53 %



## Luminaire

Code BH10905+BH16301  
Name A.39 SHARP D+IND 2368 HB 54 400K ND SIL + COVER 6X4 OPT. HB WHITE

## Measurem.


Code FTS1900571-B  
Name A.39 SHARP D+IND 2368 HB 54 400K ND SIL + COVER 6X4 OPT. HB WHITE

Luminaire Flux	11278 lm	Luminaire Power	125.0 W	Efficacy	90.224 lm/W	Efficiency	100.00%
Source Flux	11278 lm	Maximum value	639.45 cd/klm	Position	C=0.00 G=1.00	CG Double Symmetrical	
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		11278 lm	
LED Flux=14404lm LED Power=107W Eff=78% EfcLed=135lm/W EfcLum=90lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	97 99 100 45 100			D DIN 5040	C62		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.45	OC	0.49	0.98	1.47	1.96	2.45
OB	0.49	0.98	1.47	1.96	2.45	OD	0.49	0.98	1.47	1.96	2.45

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	7211.71	7160.25	6517.77	4338.90	795.09	138.21	32.38	20.69	13.58	5.07
OB	7211.71	7160.25	6517.77	4338.90	795.09	138.21	32.38	20.69	13.58	5.07
OC	7211.71	7160.25	6517.77	4338.90	795.09	138.21	32.38	20.69	13.58	5.07
OD	7211.71	7160.25	6517.77	4338.90	795.09	138.21	32.38	20.69	13.58	5.07



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0 Max non a G
1.00	0.98	7212	4340		
2.00	1.96	1803	1085		
3.00	2.94	801	482		
4.00	3.91	451	271		
5.00	4.89	288	174		

H[m]	D[m]	Max lux	Med lux	Beta=26.1°+26.1°	G=0.0 Max non a G
1.00	0.98	7212	4340		
2.00	1.96	1803	1085		
3.00	2.94	801	482		
4.00	3.91	451	271		
5.00	4.89	288	174		