

Luminaire

Code AF31601+AF95004
Name SHARP SMD.1X 3W 940 FL EXD BCO+ SCREEN 1X BLACK

Measurement

Code FTS1902075
Name SHARP SMD.1X 3W 940 FL EXD BCO+ SCREEN 1X BLACK

Luminaire Flux	212 lm	Luminaire Power	3.5 W	Efficacy	60.474 lm/W	Efficiency	100.00%
Source Flux	212 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Rectangular Luminaire		Length	41 mm	Width	45 mm	Height	90 mm
Rectangular Luminous Area		Length	37 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.001369 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000331 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		212 lm	
LED Flux=283.995lm LED Power=3.5W Eff=75% EfcLed=81lm/W EfcLum=60lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


41mm x 45mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code AF31601+AF95004
Name SHARP SMD.1X 3W 940 FL EXD BCO+ SCREEN 1X BLACK

Measurem.


Code FTS1902075
Name SHARP SMD.1X 3W 940 FL EXD BCO+ SCREEN 1X BLACK

Luminaire Flux	212 lm	Luminaire Power	3.5 W	Efficacy	60.474 lm/W	Efficiency	100.00%
Source Flux	212 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Rectangular Luminaire		Length	41 mm	Width	45 mm	Height	90 mm
Rectangular Luminous Area		Length	37 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.001369 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000331 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		212 lm	
LED Flux=283.995lm LED Power=3.5W Eff=75% EfcLed=81lm/W EfcLum=60lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1186.23	1008.70	309.70	82.84	4.90	1.04	0.13	0.00	0.00	0.00
OB	1186.23	1008.70	309.70	82.84	4.90	1.04	0.13	0.00	0.00	0.00
OC	1186.23	1008.70	309.70	82.84	4.90	1.04	0.13	0.00	0.00	0.00
OD	1186.23	1008.70	309.70	82.84	4.90	1.04	0.13	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	1186	757		
2.00	0.70	297	189		
3.00	1.05	132	84		
4.00	1.40	74	47		
5.00	1.75	47	30		