

## Luminaire

Code FT61001  
Name SPHERE 14 PEND.FUNIVIA OUT 930

## Measurement

Code FTS2500086  
Name SPHERE 14 PEND.FUNIVIA OUT 930

Luminaire Flux	671 lm	Luminaire Power	6.5 W	Efficacy	103.231 lm/W	Efficiency	100.00%
Source Flux	671 lm	Maximum value	105.48 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Round Luminaire		Diam.	140 mm	Height	166 mm		
Round Luminous Area		Diam.	140 mm	Height	128 mm		
Horizontal Luminous Area		0.015394 m2		Emitting area on Plane 180°		0.017920 m2	
Emitting area on Plane 0°		0.017920 m2		Emitting area on Plane 270°		0.017920 m2	
Emitting area on Plane 90°		0.017920 m2		Glare area at 76°		0.021112 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		07-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		671 lm	
LED Flux=735lm LED Power=5.7W Eff=91% EfcLed=130lm/W EfcLum=103lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	27 53 77 60 100			D DIN 5040		C11	
F UTE	0.60 J + 0.40 T			B NBN		BZ 8 / 0.8 / BZ 7	

Diam=140mm



Semipiani C

180.0 ——— 0.0

ULOR 39.84 %

DLOR 60.16 %

RN 39.84 %

