

Luminaire


Code FW12004APP
Name DIFFUSED LINEAR 1200 FUNIVIA 940 NRO

Measurem.

Code FTS2300050-B
Name DIFFUSED LINEAR 1200 FUNIVIA 940 NRO

Luminaire Flux	2509 lm	Luminaire Power	26.0 W	Efficacy	96.500 lm/W	Efficiency	100.00%
Source Flux	2509 lm	Maximum value	349.78 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1200 mm	Width	20 mm	Height	20 mm
Rectangular Luminous Area		Length	1176 mm	Width	18 mm	Height	0 mm
Horizontal Luminous Area		0.021168 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005121 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-01-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2509 lm	
LED Flux=4392lm LED Power=24W Eff=57% EfcLed=184lm/W EfcLum=97lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	47 79 96 100 100			D DIN 5040	A30		
F UTE	1.00 E			B NBN	BZ 5 / 2 / BZ 4		

1200mm x 20mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.01 %

DLOR 99.99 %

RN 0.01 %

