

Luminaire


Code 1861030APP
Name DREISPITZ 90 C/W DIF BLK APP

Measurem.

Code FTS2500024
Name DREISPITZ 90 C/W DIF BLK APP

Luminaire Flux	2137 lm	Luminaire Power	20.0 W	Efficacy	106.850 lm/W	Efficiency	100.00%
Source Flux	2137 lm	Maximum value	175.50 cd/klm	Position	C=40.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	822 mm	Width	99 mm	Height	74 mm
Rectangular Luminous Area		Length	810 mm	Width	60 mm	Height	29 mm
Horizontal Luminous Area		0.048600 m2		Emitting area on Plane 180°		0.024300 m2	
Emitting area on Plane 0°		0.024300 m2		Emitting area on Plane 270°		0.001800 m2	
Emitting area on Plane 90°		0.001800 m2		Glare area at 76°		0.035336 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2137 lm	
LED Flux=2953lm LED Power=17W Eff=72% EfcLed=171lm/W EfcLum=107lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	37 65 85 68 100			D DIN 5040	B21		
F UTE	0.68 H + 0.32 T			B NBN	BZ 6		

822mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 31.78 %

DLOR 68.22 %

RN 31.78 %

