

Luminaire


Code 1862030APP
Name DREISPITZ 120 C/W DIF BLK APP

Measurem.

Code FTS2500040
Name DREISPITZ 120 C/W DIF BLK APP

Luminaire Flux	2939 lm	Luminaire Power	28.0 W	Efficacy	104.964 lm/W	Efficiency	100.00%
Source Flux	2939 lm	Maximum value	175.50 cd/klm	Position	C=40.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1132 mm	Width	99 mm	Height	74 mm
Rectangular Luminous Area		Length	1120 mm	Width	60 mm	Height	29 mm
Horizontal Luminous Area		0.067200 m2		Emitting area on Plane 180°		0.033600 m2	
Emitting area on Plane 0°		0.033600 m2		Emitting area on Plane 270°		0.001800 m2	
Emitting area on Plane 90°		0.001800 m2		Glare area at 76°		0.048859 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2939 lm	
LED Flux=4060lm LED Power=24W Eff=72% EfcLed=171lm/W EfcLum=105lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	37 65 85 68 100			D DIN 5040	B21		
F UTE	0.68 H + 0.32 T			B NBN	BZ 6		

1132mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 31.78 %

DLOR 68.22 %

RN 31.78 %

